


程陽有限公司

住址：台北縣新莊市復興路三段109號
Tel:(02)8993-1730 Fax:(02)8993-1732

<p>構造 CONSTRUCTION</p>	<p style="text-align: center;">Silicone Adhesive</p> 	<p>樣品 SAMPLE</p>	<p>1.顏色Color: 琥珀色Amber 2.總厚Total thickness: 0.13mm 3.長度Length: 依客戶需求 4.寬度Width: 依客戶需求</p>
<p>I.產品物性 (The Properties of Tape)</p>			
<p>1.初期力Tack (PSTC-6): 6 cm ↓ 2.保持力Cohesion force(PSTC-7): 24 ↑ hrs/1"*1" 3.膠厚Coating thickness: 基板面 50 μ 治具面 30 μ 4.耐電蝕係數Electrolytic Corrosion Coefficient:1.0 5.粘著力Adhesion(PSTC-1): 基板面 1 kg/25mm 治具面 0.06 kg/25mm 6.剝離力Unwinding force(PSTC-4): 基板面 30g/25mm 治具面10g/25mm</p>		<p>7.耐電壓Breakdown : 100-150 KV/mm 8.Volume.Resistance (ASTM D257): 1.4*10⁶ MΩ 9.Surface Resistance (ASTM D257): 2.0*10⁷ MΩ 10.適用溫度Temp. range: 280°C (1hr) 11.耐酸鹼 solvent resistance: OK 12 本產品可多次重覆使用 13 適用無鉛製程 耐高溫 不殘膠</p>	